

# SPC RIGID floor with underlay

## Canadian Design

### technical sheet

**Material:** 100% pure PVC with admixture of calcium calcite (powder)

**Logistics data:** Package: 1,7712 m<sup>2</sup> / 8 pcs  
Package weight: 15,23 kg  
Palette: 127,5264 m<sup>2</sup> / 72 pkg.  
Paletteweight: 1096,56 kg

**Floor type:** Click vinyl panels with 2G Valinge lock

**Thermal conductivity:** EN 12524: 0,11 W/mK

**Thickness:** 5.0mm (1.0mm washer)

**Floor heating:** suitable for floor heating

**Dimensions:** Length: 1230 mm  
Width: 180 mm

**Class:** 23/33

**Wear layer:** 0,3 mm

**Resistance to soiling:** EN: class 0

**Fire resistance:** BFL-S1

**Abrasion resistance:** EB 660-2: class T

**Formaldehyde emissions:** E1

**Constant load resistance:** EN 425: compliant with the standard

**Anti-slip properties:** R9, DIN 51130

**Installation type:** floating, Click System

**Surface:** matt polyurethane surface with ceramic particles

**Structure:** wood, without V-joint

**Construction:** luxury vinyl floor, composite core with density > 2090 kg / m<sup>3</sup>

**Customs Tariff Number:** 39181090

**Dimensional stability:** EN 427: length max. 0.05 mm  
EN 434: average < 0.15%